



**VAN DYCK**  
FLOORS

NEON





# NEON

**VAN DYCK**  
FLOORS



**YELLOW**



**LIME**



**PURPLE**



**NAARTJIE**




**GREEN**




**IVORY**




**PINK**




**TURQUOISE BLUE**



**NEON PLAIN**



**RED**



**AQUA**

While every effort has been made to replicate colours in print, some slight variance may occur. Please refer to sample swatches for accurate colour references.

## Maintenance

Enhance the performance and appearance of your carpet by following these steps: • Use quality walk off mats. • Vacuum thoroughly and frequently. • Remove spills and marks immediately. • General clean by a SETA Qualified Cleaner.

## >> Helpful Hint

Whilst the light colours in the range are extremely attractive, they are high maintenance. They show soil quicker than darker colours and need frequent cleaning. We accept no liability on soiling, as this is maintenance related and not a manufacturing defect.

## TUFTED LOOP PILE TILES

Pile Fibre:	100% Aquafil BCF Nylon 6
Backing:	Enduroback (Modified Recycled Bitumen)
Fibre weight:	440gsm
Total weight:	4250gsm
Total thickness:	5mm
Protective Finish:	Stain Shield
Location grade:	Heavy Commercial
Fire rating:	2
Width/Size:	50 X 50cm
VOC Rating:	Meets requirements of green star rating (GBCSA criteria)
Country of Origin	Manufactured in South Africa from local and imported raw materials.



## Made in South Africa

Van Dyck Floors are made with pride in Durban, South Africa, since 1948 by the longest established carpet manufacturer in the country.



## 5 year guarantee

This carpet is guaranteed by Van Dyck Floors for a period of five years against any latent defect in the manufacturing process. Claims will be treated in accordance with the South African Carpet Manufacturers Standard Claims Policy. However, carpets must have been maintained and cleaned according to Van Dyck Floors' written instructions.



## 10 year warranty

Van Dyck Floors (Pty) Ltd offers a 10 year limited warranty against excessive fibre wear on this carpet.



## ISO Certification

Van Dyck Floors quality and environmental management systems are certified to SABS 9001 and SABS 14001 respectively. This is your assurance of our commitment to maintain the highest international quality standards.



## Stain Shield

The Stain Shield protection mark is your assurance that the carpet you have purchased is protected from stains and soiling. Where Stain Shield protection is not inherent in the pile fibre, Van Dyck applies an advanced fluoro carbon protection shield during the production process. Stain Shield repels oily and watery stains and soil, and gives you more time to remove the offending substance before it penetrates the pile.



## Torture Tunnel Tested

Every carpet manufactured by Van Dyck Floors undergoes this unique test during which it is subjected to 75 000 footfalls.



## Anti-allergenic

Carpeting helps trap dust and irritants, which can cause allergies. These can then be removed by regular vacuuming.



## Silver Plus Protection

The ultimate anti-microbial protection.

## Bill of Quantities

Tiles: NEON tufted tiles with Enduroback KR4 made from 100% Aquafil BCF Nylon 6 in (colour name), by Van Dyck Floors, laid in accordance with the code of practice for the installation of textile floor coverings (SANS 10186).

## Satisfaction

Due to dye lot variations and machine settings, actual material may vary from the sample. However this variation is kept within exacting standards as laid down by SANS 1375. Construction of some carpet may involve the occurrence of shift lines across the width of the carpet. Certain light sources shining across the surface may emphasise the effect of shadow lines. These are not a manufacturing defect and will not detract from the carpet's performance.

## Colour Variance

Care must be taken when ordering or installing carpeting in individual areas, as carpeting, like all textile products, is subject to shade variation between batches.

## CAUTION:

Colour fastness to light: Dyes are selected for their performance and repeatability to commercial standards, but colours can fade when exposed to harsh, direct sunlight. Adequate precautions must be taken to protect the carpet against such exposure to prevent premature fading or damage.

## Furniture

Place protectors or carpet off-cuts under furniture to prevent crushing of carpet pile and eventual damage to the backing. Rearrange furniture from time to time to allow pile to recover and change traffic paths. Use carpet protector mats for chairs with castor wheels.